

CHOOSE QUALITY, TREAT YOURSELF WITH TELELIFT EXPERTISE

A leader in the field of hydraulic ladders and telescopic Boom for 60 years, our team has the expertise to offer equipment that meets your expectations. In constant innovation, we always work with the objective of offering safe, light and optimal products according to the needs of the industry.

- TELESCOPIC BOOM
100% ELECTRIC
- MODELS WITH ACCESS DIRECTLY
FROM THE GROUND
- VERY LIGHT
- CONTINUOUS ROTATION

**CONTACT OUR SALES TEAM
TO DISCUSS YOUR PROJECT
AND YOUR NEEDS.**

TELELIFT

STEP UP FURTHER



— Telescopic Boom and hydraulic ladders designed specifically for light commercial trucks. For equipment that emphasizes safety and lightness!

TELELIFT.CA

1, RUE PARO, WARWICK, QO, CANADA, J0A 1M0
1 833 358-5444

GET ACCESS DIRECTLY FROM THE GROUND WITH OUR INNOVATIVE TELESCOPIC BOOMS WHICH PROVIDE THE BEST FEATURES FOR CARGO VANS AND TRUCKS.



THE TELESCOPIC BOOM 37 INSULATED

Our Features and Specifications

- Less than 9,050 lbs GVWR, does not require CDL
- Best pay load on the market
- No PTO required (power take off system)
- Storage maximized by its design
- No outriggers required
- Continuous rotation
- Independent electric power source which makes it 100% electric



Working height*	Starting at 35'	10.66 m
On-road retracted height		
Truck height 7'	10'7"	3.25 m
Truck height 9'	12'7"	3.84 m
Truck height 10'	13'7"	4.14 m
Reach	25'	7.62 m
Equipment weight	2043 lbs	926 kg
Basket capacity**	300 lbs	136 kg
Rotation		Continue
Hydraulic pressure		2000 PSI
Elevation angle		-8 to 78
GVWR of the required vehicle	9900 lbs	4490 kg

*Configuration with Ford Transit van.
** 350 lbs with HD option on some truck models



THE TELESCOPIC BOOM 41

INSULATED

Working height*	Starting at 44'	13.4 m
On-road retracted height		
Truck height 7'	10'7"	3.25 m
Truck height 9'	12'7"	3.84 m
Truck height 10'	13'7"	4.14 m
Reach	31'	9.4 m
Equipment weight	1995 lbs	904 kg
Basket capacity**	300 lbs	136 kg
Rotation		Continue
Hydraulic pressure		2000 PSI
Elevation angle		-7 to 78
GVWR of the required vehicle		N/A

*Configuration with Ford Transit van.
** 350 lbs with HD option on some truck models

"SAFETY IS AT THE TOP OF OUR PRIORITIES" WHEN WE DESIGN OUR TELESCOPIC BOOM AND HYDRAULIC LADDERS.

We know that safety is at the heart of the concerns of operators of smaller trucks, which is why we offer a range of varied products that take this into account.

Other model of hydraulic ladders are offered. Contact our team who will be able to recommend what is best for your needs.



THE HYDRAULIC LADDERS TTS 37

INSULATED

Working height*	Starting at 37'	11.28 m
On-road retracted height		
Truck height 7'	10'6"	3.18 m
Truck height 9'	12'6"	3.78 m
Truck height 10'	13'6"	4.09 m
Reach	27'	8.23 m
Equipment weight	1881 lbs	853 kg
Basket capacity**	300 lbs	136 kg
Rotation		Continue
Hydraulic pressure		2000 PSI
Elevation angle		-8 to 78
GVWR of the required vehicle	9900 lbs	4490 kg

*Configuration with Ford Transit van.
** 350 lbs with HD option on some truck models

